




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04L 12/66, 29/06		A1	(11) International Publication Number: WO 97/28629
			(43) International Publication Date: 7 August 1997 (07.08.97)
(21) International Application Number: PCT/SE97/00138		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 29 January 1997 (29.01.97)			
(30) Priority Data: 9600332-2 30 January 1996 (30.01.96) SE			
(71) Applicant (for all designated States except US): TELEFONAKTIEBOLAGET LM ERICSSON [SE/SE]; S-126 25 Stockholm (SE).			
(72) Inventors; and			
(75) Inventors/Applicants (for US only): BJÖRKQVIST, Mikael [SE/SE]; Myrstuguvägen 263, S-143 32 Värby (SE). HUSTAD, Randi [NO/NO]; Høviksvingen 16A, N-1322 Høvik (NO).			
(74) Agents: HERBJÖRNSEN, Rut et. al.; H. Albiñns Patentbyrå AB, P.O. Box 3137, S-103 62 Stockholm (SE).			
		<p>Published With a revised version of the international search report.</p> <p>(88) Date of publication of the revised version of the international search report: 23 October 1997 (23.10.97)</p>	

(54) Title: INTERWORKING FUNCTION



(57) Abstract

For providing an interworking function between an N-ISDN (20) and a B-ISDN (10), the B-ISDN (10) comprises a second Signalling System 7 based data communication protocol (90, 100) comprising an MTP2 level which functions are split on a first sublevel (92) and a second sublevel (MTP2higher).

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

INTERNATIONAL SEARCH REPORT

International application No.
PCT/SE 97/00138

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: H04L 12/66, H04L 29/06
According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: H04L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched
SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPAT, JAPIO, WPI

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5375118 A (RAO ET AL), 20 December 1994 (20.12.94), abstract --	1-5,7,11-15, 17
A	US 5115427 A (JOHNSON, JR. ET AL), 19 May 1992 (19.05.92), see the claims. --	1-5,7,11-15, 17
A	EP 0581087 A1 (SIEMENS AKTIENGESSELLSCHAFT), 2 February 1994 (02.02.94), claim 1, abstract --	1-5,7,11-15, 17
A	WO 9403004 A1 (ITALTEL SOCIETA ITALIANA TELECOMUNICAZIONI S.P.A.), 3 February 1994 (03.02.94), page 7, line 23 - page 8, line 32 --	1-5,7,11-15, 17

☐ Further documents are listed in the continuation of Box C. ☒ See patent family annex.

- * Special categories of cited documents:
- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed
- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- "&" document member of the same patent family

Date of the actual completion of the international search

24 April 1997

Date of mailing of the international search report

14-08-1997

Name and mailing address of the ISA/
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Authorized officer

Friedrich Kühn
Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

Information on patent family members

06/08/97

International application No.

PCT/SE 97/00138

Patent document cited in search report			Publication date	Patent family member(s)	Publication date
US	5375118	A	20/12/94	EP 0584687 A	02/03/94
US	5115427	A	19/05/92	AT 132315 T	15/01/96
				CA 2036744 A,C	01/10/91
				DE 69115740 D,T	15/05/96
				EP 0450819 A,B	09/10/91
				SE 0450819 T3	
				ES 2081431 T	01/03/96
				JP 4225649 A	14/08/92
EP	0581087	A1	02/02/94	DE 4225389 C	30/09/93
				FI 933411 A	01/02/94
WO	9403004	A1	03/02/94	DE 69309471 D	00/00/00
				EP 0653132 A,B	17/05/95
				SE 0653132 T3	
				IT 1259036 B	11/03/96
				IT MI921806 D	00/00/00



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04L 12/66, 23/06	A1	(11) International Publication Number: WO 97/28629
		(43) International Publication Date: 7 August 1997 (07.08.97)

(21) International Application Number: PCT/SE97/00138

(22) International Filing Date: 29 January 1997 (29.01.97)

(30) Priority Data:
9600332-2 30 January 1996 (30.01.96) SE(71) Applicant (for all designated States except US): TELEFONAK-
TIEBOLAGET LM ERICSSON [SE/SE]; S-126 25 Stock-
holm (SE).


(72) Inventors; and

(75) Inventors/Applicants (for US only): BJÖRKQVIST, Mikael
[SE/SE]; Myrstuguvägen 263, S-143 32 Vårby (SE). HUS-
TAD, Randi [NO/NO]; Høviksvingen 16A, N-1322 Høvik
(NO).(74) Agents: HERBJÖRNSSEN, Rut et al.; H. Albiñs Patentbyrå
AB, P.O. Box 3137, S-103 62 Stockholm (SE).(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR,
BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE,
HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS,
LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL,
PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA,
UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ,
UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ,
TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR,
GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF,
BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

Published

With international search report.

(54) Title: INTERWORKING FUNCTION



(57) Abstract

For providing an interworking function between an N-ISDN (20) and a B-ISDN (10), the B-ISDN (10) comprises a second Signalling System 7 based data communication protocol (90, 100) comprising an MTP2 level which functions are split on a first sublevel (92) and a second sublevel (MTP2higher).

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

INTERWORKING FUNCTION

The invention relates to data communication networks. In particular it relates to packet-switching networks and to the aspect of such networks interworking.

Definitions of some used terms and abbreviations

(STALLINGS, William, Data and Computer Communications; Macmillan Publishing Company; 1991; and DE PRYCKER, Martin, Asynchronous Transfer Mode: Solution for broadband ISDN; Ellis Horwood series in computer communications and networking; 1991; both herein incorporated by reference)

ISDN: Integrated Services Digital Network;

N-ISDN: Narrowband-ISDN;

SS7: Signalling System Number 7 is a layered set of protocols that is used for control communication internal to a digital network, e.g. an N-ISDN, and provides facilities for establishing, maintaining and terminating connections. It comprises in total four levels;

N-ISUP: N-ISDN User Part and the fourth level of SS7. It provides for the control signalling needed in an N-ISDN to deal with N-ISDN subscriber calls and related functions;

MTP: Message Transfer Part, lower three levels of SS7, provides a reliable but connectionless service for routing messages through the SS7 network, whereby

MTP1 is the Signalling data link and the first level of SS7.;

MTP2 is the Signalling link and the second level of SS7. This level is specified in the ITU-T Recommendation Q.703 (03/93) and is herein incorporated by reference. According to the ITU-T Recommendation Q.703 (03/93) the signalling link functions, together with a signalling data link as bearer, provide a signalling link for reliable transfer of signalling messages between two directly connected signalling points. Signalling messages delivered by superior hierarchical levels are transferred over the signalling link in variable length signal units. A signal unit is constituted of a variable length signalling information field which carries the information generated by a user Part and a number of fixed length fields which carry information required for message

transfer control. In the case of link status signal units LSSU, the signalling information field and the service information octet is replaced by a status field which is generated by the signalling link terminal. There are three types of signal unit, i.e. the message signal units MSU, link status signal units LSSU and fill-in signal units FISU. The signalling link functions comprise signal unit delimitation, signal unit alignment, error detection, error correction, initial alignment, signalling link error monitoring and flow control. All these functions are coordinated by the link state control;

MTP3 is the Signalling network and the third level of SS7

10 HDLC: HDLC uses synchronous transmission. All transmissions are in frames, and a single frame format suffices for all types of data and control exchanges. The frame has the following fields: Flag, Address; Control; Information; Frame check sequence (FCS); and Flag. Bit stuffing is a procedure which is used for providing data transparency.

15 B-ISDN: Broadband-ISDN is a service or system requiring transmission channels of supporting rates greater than the primary rates;

B-ISUP: B-ISDN User part;

ATM: Asynchronous Transfer Mode (protocol) is a transfer mode solution for implementing a B-ISDN, comprising three layers defined as
20 the physical layer PHY which mainly transports information;
the ATM layer which mainly performs switching/routing and multiplexing;
and
the ATM adaptation layer (AAL) which is mainly responsible for adapting service information to the ATM stream;

5 ST: Signalling terminal;

ET: Exchange terminal;

IWF/IWU: Interworking function/Interworking unit;

NNI: Network to Network interface;

Node: to which stations attach, is the boundary of a communication network, e.g. a
30 B-ISDN network, and the node is capable of transferring data between pairs of attached stations.

Description of the Related Art

Both information and parameters are sent from and received by an N-ISDN using the SS7 protocol and are furthermore transmitted in a HDLC (High Level Data Link Control) based frame format, e.g. HDLC or LAP-D. The SS7 and the HDLC based frame format are well known in the art. A B-ISDN, however, sends and receives information and parameters using an ATM protocol which is a specific packet oriented transfer mode based on fixed length cells. The ATM protocol is well known in the art. The difficulty in sending data from one type of network to another resides in the use of different protocols and data formats, frames or cells, required for these protocols.

Special interworking units/functions IWU/IWF have been developed for solving the problem of interworking between N-ISDN and B-ISDN. The interworking is performed either by an Interworking Unit, IWU which is a unit separate from the B-ISDN or an Interworking Function, IWF which is an integral part of the B-ISDN. IWU/IWF are specified in the ITU-T Recommendation I.580 from 03.93: "General Arrangements for Interworking between B-ISDN and 64 kbits/s based ISDN". Accordingly a standard NNI is the interface between the 64 kbits/s ISDN, i.e. the N-ISDN, and the IWU/IWF and between the B-ISDN and the IWU/IWF. EP-A-0 581 087 discloses an N-ISDN and a B-ISDN interworking by means of an IWU. The advantage of IWU/IWF is that they are standardised. However, they need a large processing capacity. They are furthermore highly dependent on market adaptations. This entails considerable costs.

Summary

It is an object of the invention to provide an interworking function which needs less processing capacity.

It is a further object of the invention to provide an interworking function which is less dependent on the market adaptations.

It is yet another object of the invention to provide an interworking function which is low in cost.

These and other objects and advantages are obtained according to the invention as

disclosed in independent claim 1 and claim 11. Preferred embodiments of the invention are given in the dependent claims.

Brief description of the drawings

Preferred embodiments of the invention will now be explained in greater detail, referring to the drawings in which

- Fig. 1 is a schematic view of networks interworking according to the prior art;
Fig. 2 is a schematic view of networks interworking according to an embodiment of the invention;
Fig. 3 is a schematic drawing of the interworking function according to an embodiment of the invention;
Fig. 4 is a flow diagram illustrating the split MTP2 layer according to an embodiment of the invention;
Fig. 5 is a schematic drawing illustrating the functions of the split MTP2 layer according to an embodiment of the invention.

Detailed description of the embodiments

Figure 1 is a schematic view of a B-ISDN 10 and an N-ISDN 20 interworking according to the prior art.

Figure 2 is a schematic view of networks signalling interworking according to an embodiment of the invention. An ATM-based network 10, e.g. a B-ISDN, and a SS7-based network 20, e.g. N-ISDN, are interworking by means of an interworking unit 60 comprised in the B-ISDN, for ensuring that a standard NNI is the only interface between the N-ISDN and the B-ISDN.

Figures 3a and 3b show two schematic drawings of a B-ISDN 10 and an N-ISDN 20 interworking. In Figure 3a a B-ISDN 10 can be seen comprising an exchange terminal ET 90 coupled to an ATM-based switch core 70 which is coupled to a signalling link terminal ST 100. A signalling link terminal refers to the means for performing all of

the functions defined at level 2 regardless of their implementation. When interworking with a B-ISDN 10, the N-ISDN 20 is coupled to the exchange terminal ET 90 of the B-ISDN 10. A means for achieving the objects of the invention is to provide the B-ISDN 10 with a means for interworking for supporting N-ISDN subscriber calls and related functions within the B-ISDN 10. Figure 3b describes more specifically the means for interworking. Therein can be seen that the second MTP level of the SS7 80, i.e. MTP2, is split into two sublevels, MTP2lower 92 and MTP2higher 103. The MTP2lower 92 is preferably situated in the exchange terminal ET 90 and the MTP2higher 103 in the signalling terminal ST 100. The functions of the MTP2 are thereby split between the MTP2lower 92 and the MTP2higher 103.

When an application X of the N-ISDN 20 has a message to an application Y of the N-ISUP supported within the B-ISDN 10, it transfers those data to the N-ISUP 81 of the SS7 80 used in the N-ISDN 20. Parameters containing the required information for the N-ISUP protocol are appended to those data and is passed as a unit together with the data to the MTP3. This process continues down through MTP2 which generates a unit called frame using e.g. a HDLC based protocol. The frame is then passed by the MTP1 onto the transmission medium. When the frame is received by the B-ISDN 10 it ascends to the MTP1 of the exchange terminal ET 90. The MTP1 91 strips off the outermost parameters, acts on the protocol information contained therein, and passes the remainder up to the next layer MTP2lower 92. MTP2lower 92 strips off the outermost parameters, acts on parts of the protocol information contained therein in accordance with an embodiment of the invention, and passes the remainder to the AAL 93. Parameters are appended to the data that contains the required information for the AAL 93 protocol. In substance one can say that the AAL 93 protocol is a protocol for packeting and segmenting data into cells on transmission and reassembling the data from cells on reception. The cells are then passed by the ATM layer 94 onto the transmission medium and switched by the ATM switch core 70 to be received by an ATM layer 101. The ATM layer 101 strips off the outermost parameters, acts on the protocol information contained therein, and passes the remainder up to the AAL 102. On reception, the AAL 102 reassembles the data from cells in accordance with its protocol and passes the data up to the MTP2higher 103. MTP2higher 103 strips off the outermost parameters, acts on the remaining parts of the MTP2 protocol information contained therein in accor-

dance with an embodiment of the invention, and passes the remainder to the MTP3 104. The MTP3 104 strips off the outermost parameters, acts on the protocol information contained therein, and passes the remainder to the N-ISUP 105. The process continues through N-ISUP 105 for transferring the message of application X to application Y. When application Y has a message for application X, the reverse process occurs.

In a preferred embodiment of the invention, the exchange terminal ET 90 comprised within the B-ISDN 10, comprises the MTP1 level 91, the MTP2lower 92, an ATM layer 93 and an AAL 92, e.g. AAL5 which is the AAL for Variable Bit Rate VBR. The signalling terminal ST 100 comprises an ATM layer 101, an ATM adaptation layer 102, e.g. AAL5 101, MTP2higher 103, MTP3 104 and N-ISUP 105.

In Figure 4 the main functions of MTP2 are shown. In a broad outline: Signal unit delimitation and alignment provide the functions for bit stuffing, insertion and removal of flags and analysis thereof; Error detection provides the functions for analysing the check bit at the end of each signal unit; Error correction provides the function of retransmission; Initial alignment provides the functions for indicating the alignment status using four different alignment status indications, i.e. status indication "O" for out of alignment (SIO), "N" for normal alignment status (SIN), "E" for emergency alignment status (SIE) and "OS" for out of service (SIOS), all indications being carried in the status field of the link status signal unit LSSU. The alignment procedure passes through a number of states during the initial alignment one of them being proving by which means the signalling link terminal validates the link's ability to carry signal units correctly by inspecting the signal units; Signalling link error monitoring provides two functions, one which is employed whilst a signalling link is in service and which provides one of the criteria for taking the link out of service, and one which is employed whilst a link is in the proving state of the initial alignment procedure. These are called the signal unit error rate monitor SUERM and the alignment error rate monitor AERM respectively; and lastly flow control for handling a level 2 congestion situation. All the above mentioned functions are coordinated by the link state control. The functions of the MTP2 and the corresponding procedures are well known in the art. Figure 4 furthermore shows how the different functions of MTP2 are split upon two sublevels in accordance with an embodiment of the invention.

Figure 5 shows the MTP2 split into two sublevels, the two sublevels being separated by a dotted line. It can be seen that the functions of MTP2lower 92 relate in general to the handling of the HDLC based frame format and the functions of MTP2higher 103 in general to error correction, retransmission and flow control of the transferred data. In particular, bit stuffing, flag detection/insertion and handling of the check sum are performed in the MTP2lower 92, whilst sequence number handling, retransmission and flow control are performed in the MTP2higher 103.

More specifically, MTP2higher 103 comprises means for error control and correction 120, 130, 140 and means for flow control 130, 150, 160, e.g. buffering means. Link control functions are split between the MTP2lower 92 and the MTP2higher 103 in that regarding alignment it is performed in the MTP2higher 103 except the proving part which is performed in the MTP2lower 92. Status control is performed in the MTP2higher 103 except for the status detection which is performed in the MTP2lower 92. Furthermore, the reliable exchange of message signalling unit MSU is not effected by the split of the MTP2. The sequence control in MTP2 is located in the MTP2higher 103 and will function in the same way as without the split.

Figure 5 shows the functions of the MTP2 layer and how they are distributed between the MTP2lower 92 and the MTP2higher 103. When transferring data from lower to higher layers, MTP2lower 92 receives data from MTP1, strips off the outermost parameters and acts on the protocol information contained therein. It removes the bit stuffing and detects the flags 108. The check bits are tested and removed 110. If errors are detected, a signal is sent to the MTP2 higher for error correction. When transferring data from higher to lower layers, the reverse process occurs 180, 190. Furthermore, there is in the MTP2lower 92 a signal unit error rate monitor SUERM for monitoring the status of the signalling link, e.g. the link status signal unit LSSU "in service". Upon detection of excessive error rate, an internal error signal is generated for being transferred to the MTP2higher 103. Moreover, there is an alignment error rate monitor AERM for monitoring the alignment of the signalling link, whereby only the proving state of the alignment monitoring is performed in the MTP2lower 92. If a counter reaches the error threshold during the proving period, an internal error signal is generated for being transferred to the MTP2higher 103. If the the MTP2 receives a link

status signal unit LSSU other than SIN/SIE, then the proving part of the alignment monitoring is terminated and the LSSU is passed on to the MTP2higher 103. The generated internal signals may be transferred in the control field. The error thresholds for the SUERM and AERM are parameters which are initialized at restart.

A preferred embodiment regarding error detection and link control may be implemented as following:

In the direction of transferring data from the N-ISDN 20 to the B-ISDN 10, MTP2lower 92 filters fill in signal units FISU by firstly detecting them and if a FISU is equal to the preceding FISU, then it is discarded; otherwise it is passed through to the MTP2higher 103. In addition, a FISU may regularly be passed to the MTP2higher 103 as an "I'm alive" signal. In the direction of transferring data from the B-ISDN 10 to the N-ISDN 20, the fill in signal units FISU will be inserted. To do this the MTP2lower 92 must keep the sequence numbers from the previous fill in signal unit FISU and use it for the generation of the fill in signal units FISU. The result of the filtering is that only fill in signal units FISU with relevant/new information is passed through to the MTP2higher 103.

The proving part of the alignment monitoring is handled by the MTP2lower 92, initiated by the MTP2higher 103. Proving signal units are generated by the MTP2lower 92 and the result of the proving is transferred to the MTP2higher 103.

The alignment status indications, e.g. SIOS/SIO/SIN/SIE, carried by the link status signal unit LSSU are filtered in the MTP2lower 92. When the MTP2lower 92 receives one of these link status signal units LSSU, it will repeat it until another one is received. This filtering is valid for both directions and will thus be unburdening the MTP2higher 103.

Hence, the MTP2higher 103 will be unburdened from continuous fill in signal units FISU and continuous link status signal units LSSU. However, for security in case a link signal is lost, fill in signal units FISU and link status signal units LSSU will regularly be transferred from the MTP2lower 92 to the MTP2higher 103.

MTP2higher 103 sends a signal to the MTP2lower 92 when proving of alignment should be initiated by the MTP2lower 92. A counter supervises the MTP2lower 92 when proving.

- 5 The MTP2higher 103 is informed by the MTP2lower 92 of excessive error rate during the signalling link error detection by an internal error signal.

10 The functions of the MTP2lower 92 can be implemented in a access processor of the exchange termination board 90 and the MTP2 upper in a central processor, the signalling terminal ST 100. N-ISUP termination and/or message mapping to the B-ISUP can be handled in the B-ISDN node. By N-ISUP termination in the B-ISDN node, real N-ISDN functionality can be provided within the B-ISDN.

- 15 The invention is also applicable whenever two CCSS7 based networks are interworking, i.e. MTP2 interworking with other layer 2 protocols.

Claims

1. Method for interworking between a first data communication network (20) and a second data communication network (10), said first data communication network (20) comprising a first Signalling System 7 based data communication protocol (80) and said second data communication network (10) comprising a second data communication protocol (ATM), said method comprising the steps of

- processing data in accordance with a first predetermined set of functions (MTP2lower) of a signalling link (MTP2) of a second Signalling System 7 based data communication network (90, 100) comprised by said second data communication network (10) for supporting a user of said second Signalling System 7 based data communication protocol (90, 100) within said second data communication network (10);

- adapting said processed data to said second data communication protocol (ATM) such that said data may be routed by said second data communication network (10);

- adapting said routed data to said second Signalling System 7 based data communication protocol (90, 100); and

- processing adapted data in accordance with a second predetermined set of functions (MTP2higher) of said signalling link (MTP2) of said second Signalling System 7 based data communication network (90, 100).

2. Method according to claim 1 wherein said first data communication network is an N-ISDN (20).

3. Method according to any one of claims 1 or 2 wherein said second data communication network is a B-ISDN (10).

4. Method according to any one of claims 1 or 2 wherein said second data communication network is a Signalling System 7 based data communication network (10).

5. Method according to claim 4 wherein second data communication network is an N-ISDN (10).

6. Method according to any one of claims 1 to 5 wherein said first and second Signalling System 7 based data communication protocol (80, 90, 100) handles data in accordance with a HDLC based format.

5 7. Method according to any one of claims 1 to 6 wherein said second data communication protocol (ATM) handles data in accordance with an ATM based format.

8. Method according to any one of claims 1 to 7 wherein said first predetermined set of functions (MTP2lower) handles error detection, link status detection and alignment
10 detection.

9. Method according to any one of claims 1 to 8 wherein said first sublevel (MTP2lower) as a result of said processing generates internal signals for transferring to said second sublevel (MTP2higher) for correction of said data.

15 10. Method according to any one of claims 1 to 9 wherein said second predetermined set of functions (MTP2higher) handles error correction, retransmission and flow control.

20 11. System for interworking between a first data communication network (20) and a second data communication network (10), said first data communication network (20) comprising a first Signalling System 7 based data communication protocol (80) and said second data communication network (10) comprising a second data communication protocol (ATM) and further comprising a second Signalling System 7 based data
5 communication protocol (90, 100) for supporting a user of said second Signalling System 7 based data communication protocol (90, 100) within said second data communication network (10), said second Signalling System 7 based data communication protocol (90, 100) comprising a second level (MTP2) which functions are split as a first sublevel (92) and a second sublevel (103), said system comprising:
30 - means (92) for processing data in accordance with the functions comprised in said first sublevel (92);
- means (93) for adapting said processed data to said second data communication protocol (ATM) such that said data may be routed by said second data communication

network (10);

- means (102) for adapting said routed data to said second Signalling System 7 based data communication protocol (90, 100); and

- means (103) for processing adapted data in accordance with the functions comprised in said second sublevel (103).

12. System according to claim 11 wherein said first data communication network (20) is an N-ISDN.

13. System according to any one of claims 11 or 12 wherein said second data communication network is a B-ISDN (10).

14. System according to any one of claims 11 or 12 wherein said second data communication network is a Signalling System 7 based data communication network (10).

15. System according to claim 14 wherein said second data communication network is an N-ISDN (10).

16. System according to any one of claims 11 to 15 wherein said first and second Signalling System 7 based data communication protocol (80, 90, 100) are adapted to handle data in accordance with a HDLC based format.

17. System according to any one of claims 11 to 16 wherein said second data communication protocol (ATM) is adapted to handle data in accordance with an ATM based format.

18. System according to any one of claims 11 to 17 wherein said first sublevel (MTP2lower) comprises the functions of error detection, link status detection and alignment detection.

19. System according to any one of claims 11 to 18 wherein said first sublevel (MTP2lower) as a result of said processing is adapted to generate internal signals for

transferring to said second sublevel (MTP2higher) for correction of said data.

20. System according to any one of claims 11 to 19 wherein said second sublevel (MTP2higher) comprises the functions of error correction, retransmission and flow control.




FIG. 1. (PRIOR ART)




FIG. 2




FIG. 3

MTP2 functions	MTP2 lower	MTP2 upper
Signal unit delimitation	x	
Signal unit alignment	x	
Error detection	x	
Error correction		x
Initial alignment	proving	x
Signalling link error monitoring	x	x
Link state control	state info	x
Flow control		x

FIG. 4




FIG.5

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 97/00138

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: H04L 12/66, H04L 23/06

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: H04L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPAT, JAPIO, WPI

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5375118 A (RAO ET AL), 20 December 1994 (20.12.94), abstract --	1-5,7,11-15, 17
A	US 5115427 A (JOHNSON, JR. ET AL), 19 May 1992 (19.05.92), see the claims. --	1-5,7,11-15, 17
A	EP 0581087 A1 (SIEMENS AKTIENGESELLSCHAFT), 2 February 1994 (02.02.94), claim 1, abstract --	1-5,7,11-15, 17
A	WO 9403004 A1 (ITALTEL SOCIETA ITALIANA TELECOMUNICAZIONI S.P.A.), 3 February 1994 (03.02.94), page 7, line 23 - page 8, line 32 --	1-5,7,11-15, 17

☐ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

- * "A" document defining the general state of the art which is not considered to be of particular relevance
- * "E" earlier document but published on or after the international filing date
- * "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- * "O" document referring to an oral disclosure, use, exhibition or other means
- * "P" document published prior to the international filing date but later than the priority date claimed

* "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

* "X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

* "Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

* "&" document member of the same patent family

Date of the actual completion of the international search

24 April 1997

Date of mailing of the international search report

08 -05- 1997

Name and mailing address of the ISA/
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Authorized officer

Friedrich Kühn
Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT
Information on patent family members

02/04/97

International application No.
PCT/SE 97/00138

Patent document cited in search report			Publication date	Patent family member(s)			Publication date
US	5375118	A	20/12/94	EP	0584687	A	02/03/94
US	5115427	A	19/05/92	AT	132315	T	15/01/96
				CA	2036744	A,C	01/10/91
				DE	69115740	D,T	15/05/96
				EP	0450819	A,B	09/10/91
				SE	0450819	T3	
				ES	2081431	T	01/03/96
				JP	4225649	A	14/08/92
EP	0581087	A1	02/02/94	DE	4225389	C	30/09/93
				FI	933411	A	01/02/94
WO	9403004	A1	03/02/94	EP	0653132	A,B	17/05/95
				IT	1259036	B	11/03/96
				IT	MI921806	D	00/00/00